Eaton 171316



La foto è rappresentativa



Catalog Number: 171316

Eaton Moeller® series SL4 Continuous light module; white; LED;24 ${\sf V}$

General specifications

Product Name	Catalog Number
Eaton Moeller® series SL4 Continuous	171316
light module	EAN 4015081678563
Product Length/Depth	Product Height
43 mm	75 mm
Product Width 43 mm	Product Weight 0.042 kg
Certifications	Model Code
CE	SL4-L24-W
IEC/EN 60529	
UL report applies to both US and	
Canada	
CSA-C22.2 No. 94-91	
UL File No.: E29184	
CSA-C22.2 No. 14-10	
UL Category Control No.: NKCR	
Certified by UL for use in Canada	
CSA Class No.: NKCR7	
IEC/EN 60947-5-1	
UL	
UL 508	

Features & Functions

Color

Other

Enclosure color

Black

Functions

Continuous light

Light modules

LED

Number of modules

Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)

General

Connection to SmartWire-DT No

Current consumption 0.022 - 0.033 A, at 24 V AC/DC

Degree of protection IP66 NEMA 4

Lifespan, electrical 100,000 h

Light type Continuous light

Material

Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)

Mounting position

As required

Overvoltage category

Ш

Pollution degree

3

Product Category

SL signal towers

Radiation angle

360 °

Rated impulse withstand voltage (Uimp) 4000 V AC

Shock resistance

Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Type Continuous light module

Voltage type AC/DC

Climatic environmental conditions

Ambient operating temperature - min -30 °C

Ambient operating temperature - max 60 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Electrical rating

Leakage current

0.003 A

Rated insulation voltage (Ui) 250 V

Rated operational voltage (Ue) at AC - min 24 V

Rated operational voltage (Ue) at AC - max 24 V

Rated operational voltage (Ue) at DC - min 24 V

Rated operational voltage (Ue) at DC - max 24 V

Risorse

Disegni

eaton-operating-sl4-continuous-light-dimensions.eps eaton-operating-button-sl7-continuous-light-symbol-003.eps eaton-operating-sl7-continuous-light-symbol-002.eps

eCAD model

DA-CE-ETN.SL4-L24-W

Istruzioni di installazione IL047001ZU

mCAD model

DA-CD-sl4_bfl4

DA-CS-sl4_bfl4

Report di certificazione DA-DC-00004253.pdf DA-DC-00004257.pdf



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. Tutti i diritti property of their respective riservati. Owners.



Eaton.com/socialmedia