

# Eaton 171317

Catalog Number: 171317

Eaton Moeller® series SL4 Continuous light module; yellow;  
LED;24 V



La foto è rappresentativa

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Moeller® series SL4 Continuous light module	171317
	<b>EAN</b>
	4015081679218
<b>Product Length/Depth</b>	<b>Product Height</b>
43 mm	75 mm
<b>Product Width</b>	<b>Product Weight</b>
43 mm	0.042 kg
<b>Certifications</b>	<b>Model Code</b>
CE	SL4-L24-Y
CSA-C22.2 No. 14-10	
IEC/EN 60529	
UL File No.: E29184	
CSA-C22.2 No. 94-91	
UL	
UL report applies to both US and Canada	
CSA Class No.: NKCR7	
IEC/EN 60947-5-1	
UL 508	
Certified by UL for use in Canada	
UL Category Control No.: NKCR	

## Features & Functions

### Color

Yellow

### Enclosure color

Black

### Functions

Continuous light

### Light modules

LED

### Number of modules

Max. 5 (with standard base)

Max. 10 (with base for mounting on both sides)

## General

### Connection to SmartWire-DT

No

### Current consumption

0.022 - 0.033 A, at 24 V AC/DC

### Degree of protection

NEMA 13

IP66

### Lifespan, electrical

100,000 h

### Light type

Continuous light

### Material

Cap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC)

### Mounting position

As required

### Overvoltage category

III

### Pollution degree

3

### Product Category

SL signal towers

### Radiation angle

360 °

### Rated impulse withstand voltage (Uimp)

4000 V AC

### Shock resistance

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27

### Type

Continuous light module

### Voltage type

AC/DC

## Climatic environmental conditions

Ambient operating temperature - min

-30 °C

Ambient operating temperature - max

60 °C

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

## Electrical rating

Leakage current

0.003 A

Rated insulation voltage (Ui)

250 V

Rated operational voltage (Ue) at AC - min

24 V

Rated operational voltage (Ue) at AC - max

24 V

Rated operational voltage (Ue) at DC - min

24 V

Rated operational voltage (Ue) at DC - max

24 V

## Risorse

Disegni

[eaton-operating-sl4-continuous-light-dimensions.eps](#)

[eaton-operating-sl7-continuous-light-symbol-002.eps](#)

[eaton-operating-button-sl7-continuous-light-symbol-004.eps](#)

eCAD model

[ETN.SL4-L24-Y](#)

Istruzioni di installazione

[IL047001ZU](#)

mCAD model

[DA-CD-sl4\\_bfl4](#)

[DA-CS-sl4\\_bfl4](#)

Report di certificazione

[DA-DC-00004253.pdf](#)

[DA-DC-00004257.pdf](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Eaton is a registered trademark.

All other trademarks are  
© 2024 Eaton. Tutti i diritti property of their respective  
riservati. owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)